AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method for producing a hydroxyl-modified ethylene-α-olefin copolymer, the method comprising:

mixing 100 parts by weight of an ethylene-α-olefin copolymer and 0.1 to 20 parts by weight of a peroxide having a hydroperoxy group, wherein the peroxide has a 10-hour half-life temperature and a 1-minute half-life temperature; and

heating a mixture containing the peroxide and the ethylene-α-olefin copolymer at a temperature ranging between the 10-hour half-life temperature and the 1-minute half-life temperature of the peroxide without causing cross-linking of the ethylene-α-olefin copolymer.

2. (Currently Amended) A method for producing a hydroxyl-modified ethylene- α -olefin copolymer, the method comprising:

mixing 100 parts by weight of an ethylene-α-olefin copolymer, 0.1 to 20 parts by weight of a peroxide having a hydroperoxy group and a radical generator having a radical generating group so that not more than 1 mole of the radical generating groups are present with respect to 1 mole of the hydroperoxy groups, wherein said peroxide has a 10-hour half-life temperature and said radical generator has a 10-hour half-life temperature not higher than the 10-hour half-life temperature of the peroxide; and

WATANABE ET AL. Appl. No. 10/538,869 March 9, 2006

heating a mixture containing the ethylene-α-olefin copolymer, the peroxide and the radical generator at a temperature ranging between the 10-hour half-life temperature of the radical generator and 220°C without causing cross-linking of the ethylene-α-olefin copolymer.

- 3. (Previously Presented) The method according to claim 2, wherein the peroxide is t-butyl hydroperoxide, t-amyl hydroperoxide, t-hexyl hydroperoxide, t-octyl hydroperoxide, cumene hydroperoxide or diisopropylbenzene hydroperoxide.
- 4. (Previously Presented) The method according to claim 2, wherein said mixing includes kneading.
- 5. (Previously Presented) The method according to claim 2, wherein the ethylene-α-olefin copolymer has Mooney viscosity of 10 to 250 at 100°C.
- 6. (Previously Presented) The method according to claim 2, wherein the radical generator is a compound having a 1-minute half-life temperature not higher than 195°C.
- 7. (Previously Presented) The method according to claim 2, wherein the ethylene- α -olefin copolymer is a bipolymer of ethylene and an α -olefin or a terpolymer of ethylene, an α -olefin and a diene.

WATANABE ET AL. Appl. No. 10/538,869 March 9, 2006

- 8. (Previously Presented) A hydroxyl-modified ethylene-α-olefin copolymer produced by the method according to claim 2, the modified copolymer containing 0.001 to 1 mole of hydroxyl groups per 1 kg of the modified copolymer and having Mooney viscosity of 10 to 250 at 100°C.
- 9. (Original) A hydroxyl-modified ethylene-α-olefin copolymer composition comprising: the hydroxyl-modified ethylene-α-olefin copolymer according to claim 8; and at least one member selected from the group consisting of a thermoplastic resin, a filler, an antioxidant, a light stabilizer, a plasticizer, a lubricant, a flame retardant and a colorant.
- 10. (Previously Presented) The method according to claim 1, wherein the peroxide is t-butyl hydroperoxide, t-amyl hydroperoxide, t-hexyl hydroperoxide, t-octyl hydroperoxide, cumene hydroperoxide or diisopropylbenzene hydroperoxide.
- 11. (Previously Presented) The method according to claim 1, wherein said mixing includes kneading.
- 12. (Previously Presented) The method according to claim 1, wherein the ethylene- α -olefin copolymer has Mooney viscosity of 10 to 250 at 100°C.
- 13. (Previously Presented) The method according to claim 1, wherein the ethylene- α -olefin copolymer is a bipolymer of ethylene and an α -olefin or a terpolymer of ethylene, an α -olefin and a diene.

WATANABE ET AL. Appl. No. 10/538,869 March 9, 2006

14 (Previously Presented) A hydroxyl-modified ethylene-α-olefin copolymer produced by the method according to claim 1, the modified copolymer containing 0.001 to 1 mole of hydroxyl groups per 1 kg of the modified copolymer and having Mooney viscosity of 10 to 250 at 100°C.

15. (Previously Presented) A hydroxyl-modified ethylene-α-olefin copolymer composition comprising:

the hydroxyl-modified ethylene-α-olefin copolymer according to claim 14; and at least one member selected from the group consisting of a thermoplastic resin, a filler, an antioxidant, a light stabilizer, a plasticizer, a lubricant, a flame retardant and a colorant.

- 16. (New) The method according to claim 1, wherein said heating includes replacing a hydrogen atom of the ethylene- α -olefin copolymer by a hydroxyl group of the peroxide having a hydroperoxy group.
- 17. (New) The method according to claim 2, wherein said heating includes replacing a hydrogen atom of the ethylene-α-olefin copolymer by a hydroxyl group of the peroxide having a hydroperoxy group.